

TECHNICAL DATA



Aid Silicone Spray

Product Description and Purpose

Aid is a clear lubricant and preservative, specially formulated to leave a slippery, continuous film that facilitates a wide range of applications. Non-drying formula lubricates, protects and lengthens life of all rubber parts. Thick viscous film adheres to most surfaces like a magnet. Temperature range works from -58°F to +600°F. Protects metal finish from rust and corrosion. **Aid** is designed to penetrate the surface pores of synthetic plastics, rubbers, neoprene, wood, fabrics, etc.

Features/Benefits

- Concentrated Release Agent
- Prevents Sticking
- Reduce Friction
- Exclusively for Use in the Manufacturing Process
- Used in Food Processing Facilities

General Usage Directions

Hold **Aid** can 8 to 10 inches from surface to be treated. Avoid over-spray. Remove any excess with a clean cloth.

For Metal Surfaces: Before application, clean using steel wool and wipe with solvent if necessary.

For Rubber Surfaces: Clean with detergent solution and wipe dry.

Uses: Garment cutting tables, sewing machines, needle lube, hand iron, packaging and processing equipment, heat sealing equipment, wrapping equipment.

NOTE: Certain plastics and painted surfaces may be softened or damaged by this spray. Test on an inconspicuous area prior to general use.



1204 SW Jefferson Street
Lee's Summit, MO 64081
816-524-1304
Fax: 816-524-3260
www.ckinc.com

TECHNICAL DATA



Physical Properties

Form	Aerosol
Color	Clear
Odor	Characteristic

Caution

Keep out of reach of children. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Safety Data Sheets for more information.



1204 SW Jefferson Street
Lee's Summit, MO 64081
816-524-1304
Fax: 816-524-3260
www.ckeinc.com